



Blank Filler Plates

Features:

- Attaches horizontally to uprights to fill unused rack mount space
- Provides a clean installation*
- Constructed of 16-gauge steel

Catalog No.	19"	23"	Mounting spaces (1.75")	A	Ship Weight
BF-19-1D		BF-23-1D	1	1.75"	1 lb
BF-19-2D		BF-23-2D	2	3.50"	2 lbs
BF-19-3D		BF-23-3D	3	5.25"	2 lbs
BF-19-4D		BF-23-4D	4	7.00"	3 lbs
BF-19-5D		BF-23-5D	5	8.75"	3 lbs

*Dove gray finish. Mounting hardware included.



WMBB-12

Wall Mount Buss Bars

Homaco Wall Mount Buss Bars mount to the wall to provide a central ground point for telecommunications equipment. The insulated ground bars protect cables entering the building from destructive electric activity. *Note: Effective grounding is a measure of continuity; be sure to use an appropriate grounding system as required by the installation.*

Features:

- The preassembled buss bar kit includes:
 - 1 qty, 1/4" thick wall buss bar
 - 2 qty, insulators
 - 2 qty, standoff brackets and hardware
- 7/16" diameter lug holes
- Accommodates 3/4", 1", and 1-3/4" center-to-center spaced two hole lugs
- Buss bar constructed of electrolytic tough pitch 110 alloy copper bar
- Insulators constructed of glass reinforced thermoset polyester
- Provides 2-3/4" standoff from back board
- 3/8" wall mounting hardware not included
- Listed to UL 467

Catalog No.	Dimensions	Number of Holes*	Ship Weight
WMBB-12	4.00"H x 12.00"W x 2.75"D	15	5 lbs
WMBB-20	4.00"H x 20.00"W x 2.75"D	51	8 lbs

*Mounting holes not included in total.



Ground Strap

Homaco Ground Straps provide grounding between spliced runway. Simply pre-drill runway to accept the strap, and connect to runway sections using compression lugs. *Note: Effective grounding is a measure of continuity; be sure to use an appropriate grounding system as required by the installation.*

Features:

- All compression lugs and 1/4-20" hardware included:
 - 1 qty, 8" ground strap
 - 2 qty, compression lugs
 - 2 qty, toothed lock washers
 - 2 qty, hex nuts
- Constructed of flexible tinned copper flat braid

Catalog No.	Dimensions*	Ship Weight
GS-8	8.75"L x 0.63"H	1 lb

*Lug hole-to-lug hole length is 8.00". Runway clearance hole for 1/4-20" is needed to mount Ground Strap.