



The **50M-2700LH Frame** terminates 2,700 pairs and is equipped with H89 brackets already installed to save time at the job site.



The **50M-2700XN Frame** terminates 2,700 pairs and is equipped with H89 brackets already installed to save time at the job site.

50M Series Single-Sided Floor Frames

Homaco 50M Single-Sided Floor Frames will help you save space, reduce cabling and jumpering costs and build consistency in your installations. When placed against the wall, the frames extend out just 14-3/4" to terminate 2,700 pairs. The patented frames are equipped with three modules to accommodate any block that mounts in an H89 bracket. Modules feature rounded edges to prevent damage to cables and jumpers during the installation. The frames are versatile — choose 4" vertical channels or 6" channels for extra capacity. Plus, single-sided frames can become double-sided frames right on the spot. For add-ons, frames can be junctioned together for a neat, organized look.

Features:

- For main distribution, centralized station equipment or PBX applications
- 50M single-sided frames terminate 2,700 pairs
- Mounts any block that fits in an H89 bracket
- Blocks positioned for convenient installer access
- Available with H89 brackets factory installed to reduce on-site labor costs
- Separate horizontal and vertical jumper paths provide clearly defined jumper routing and quick tracing, reducing installation time
- Built-in horizontal rings keep jumpers organized
- 4" vertical channels or 6" to provide extra cable capacity
- Velcro® cable retainers manage vertical cables in channel uprights
- Frames can be junctioned together in multiple-frame lineups
- Pre-assembled and ready to go right out of the box
- Pre-terminated frames also are available
- Includes 12" cable runway support

Specifications:

- 6061-T6 structural grade aluminum uprights
- Drilled and tapped on both sides
- 5/8" floor anchoring holes on base feet
- Eight locations for attaching a ground
- Listed to the UL 1863 Standard for Communication Circuit Accessory

Homaco Hint:

Ground your equipment using Homaco's ground bar. See page 68.

Catalog No.	Block Capacity*	No. of Pairs	Dimensions	Ship Weight
50M Series Single-Sided Floor Frames				
50M-2700LN	54	2,700	84.00"H x 35.50"W x 18.25"D	105 lbs
50M-2700XN	54	2,700	84.00"H x 35.50"W x 13.75"D	95 lbs

*Blocks are not included. L = patented 6" channels; X = 4" channels. Other block types can also be mounted.

50M Series Single-Sided Floor Frames with H89 Brackets

50M-2700LH	54	2,700	84.00"H x 35.50"W x 18.25"D	115 lbs
50M-2700XH	54	2,700	84.00"H x 35.50"W x 13.75"D	105 lbs

L = patented 6" channels; X = 4" channels. Other block types can also be mounted.

50M Series Modules & Base Angle Set

Homaco provides individual modules for X series and L series 2,700-pair frames. Modules are equipped with pre-installed H89 brackets. To order blocks, see page 66.

Catalog No.	Block Capacity*	No. of Pairs	Dimensions	Ship Weight
Add-on module for 50M-2700X				
50M-900	18	900	27.12"H x 35.25"W x 7.25"D	26 lbs
Add-on module for 50M-2700L				
50M-900L	18	900	27.12"H x 35.25"W x 9.56"D	26 lbs

*Blocks are not included. Each module is equipped with H89 brackets. L = Added cabling and jumpering space.

Base Angle Set

50L-1224			3.50"H x 2.00"W x 6.00"D	1 lb
-----------------	--	--	--------------------------	------