

KRONE Block Floor Frames

KRONE Floor Frames are available with two different modules – one mounts five KRONE backmounts across (the K5 module) and the other mounts six across (K6 module). Both modules route cables behind the jumper fields. Separate horizontal and vertical pathways are designated for jumpering. Our KRONE frame will give the density needed without sacrificing jumper space or good cable management practices.

KRONE Floor Frames are equipped with three modules per side. KRONE Floor Frames will help save space, reduce cabling and jumpering costs and build consistency in installations.

Features:

- For main distribution, centralized station equipment or PBX applications
- Modules positioned for convenient installer access
- Separate horizontal and vertical jumper paths provide clearly defined jumper routing and quick tracing
- 6" vertical channels provide extra cable capacity
- Velcro® cable retainers manage vertical cables in channel uprights
- Available single-sided or double-sided
- Frames can be junctioned together in multiple-frame lineups
- Pre-assembled and ready to go right out of the box

Specifications:

- 6061-T6 structural grade aluminum uprights
- Drilled and tapped on both sides
- 5/8" floor anchoring holes on base feet
- Eight locations for attaching a ground
- Listed to the UL 1863 Standard for Communication Circuit Accessory

Catalog No.	Back Mount Capacity	Dimensions	Ship Weight
Single-Sided			
50M-2700L-K5	15	84.00"H x 35.50"W x 18.25"D	105 lbs
50M-2700L-K6	18	84.00"H x 35.50"W x 18.25"D	105 lbs
Double-Sided			
50M-5400L-K5	30	84.00"H x 35.50"W x 25.25"D	160 lbs
50M-5400L-K6	36	84.00"H x 35.50"W x 25.25"D	160 lbs

K5 = mount five KRONE backmounts across; K6 = mount six KRONE backmounts. KRONE backmounts and blocks are not included.

Krone Modules

When your Krone Single-Sided Frame installation requires add-ons beyond the capacity of a single-sided frame, convert the frame by adding additional modules.

Catalog No.	Block Capacity*	No. of Pairs	Dimensions	Ship Weight
Add-on module for 50M-2700L-K5				
50M-900WLK5	5	1050	27.31"H x 35.25"W x 9.56"D	15 lbs
Add-on module for 50M-2700L-K6				
50M-900WLK6	6	1008	27.31"H x 35.25"W x 9.56"D	15 lbs

**Blocks are not included. L = Added cabling and jumpering space.*

Krone Frame/Module Guide

Krone 21 Position Mounting Bracket	Krone Block Pair	Pairs per Krone Bracket	Homaco Module Style	Pairs per module	Single-Sided Frame Loaded	Double-Sided Frame Loaded
Type 105	10	210	K5	1050	3150	6300
Type 85	8	168	K6	1008	3024	6048

** KRONE backmounts and blocks are not included.*



KRONE backmounts are easily installed on Homaco KRONE Block Floor Frames.



The K6 Module mounts six KRONE backmounts across and also has been adapted for wall installations (see page 63).*



The K5 Module mounts five KRONE backmounts across. It also is available for wall installations (see page 63).*